




HEAVY DUTY
 fully drivable
 solid top/bottom

MEDIUM DUTY
 pedestrian
 solid/drainage top | open bottom

RAMP

TILE IMAGE			
TILE SIZE	<p>ACTUAL 43.3" x 43.8" x 1.6" 110cm x 111cm x 4cm</p> <p>USABLE AREA 39.4" x 39.4" 100cm x 100cm</p>		<p>HEIGHT 1.6" 4cm</p> <p>WIDTH 18.5" 47cm</p> <p>LENGTH 19.7" 50cm</p>
WEIGHT	<p>HD SOLID BOTTOM 30.7lbs 13.93kg</p>	<p>MD OPEN BOTTOM 22.6lbs 10.25kg</p>	<p>OPEN BOTTOM RAMP 4.6lbs 2kg</p>
WEIGHT CAPACITY	<p>HD SOLID BOTTOM 585 PSI</p>	<p>MD DRAINAGE 482 PSI</p> <p>MD OPEN BOTTOM 514 PSI</p>	<p>OPEN BOTTOM RAMP 514 PSI</p>
FLAMMABILITY	ASTM E84 Class C UL 94HB	ASTM E84 Class C UL 94HB	ASTM E84 Class C UL 94HB
COLOR	Translucent or Dark Gray	Translucent or Dark Gray	Translucent or Dark Gray
MATERIAL	High-density polyethylene with structural modifiers		
DESIGN FEATURES	<ul style="list-style-type: none"> • Translucent allows light penetration to surface below • Toolless assembly • Internal honeycomb structure for strength • Includes UV inhibitors to prevent discoloration and preserve strength and flexibility in sunlight • Tiles can withstand various climates; avoid extreme temperatures for optimal longevity • Temperature-adaptive connection system allows expansion and contraction without affecting durability • Drainage tiles are designed to allow air and water to flow through 		Meets ADA compliance requirements
CONNECTION SYSTEM	Interlocking flange and self-aligning		<p>Interlocking flange panel</p> <p>Attach along any connection point</p>
SHIPPING INFO	<ul style="list-style-type: none"> • 54 tiles per standard pallet (581 ft² 54 m²) • 20 pallets per 40ft ISO container (11,625 ft² 1,080 m²) • 26 pallets per semi truckload (15,113 ft² 1,404 m²) 		